

JC20 REC'D PCT/PTO 25 OCT 2009

What is claimed is:

1. A pipe fixing system for inserting and fixing a pipe thereto, which forms a base part of a pipe structure,
5 comprising:

a body (20) having a stopping part (21) formed on the lower portion of the inside thereof for stopping the pipe (10) inserted into the body. (20) an extended portion extended partially upwardly from the stopping part (21)
10 toward an upper end of the body (20) for supporting the pipe (10) and closely contacting the outer peripheral surface of the pipe (10), a tapered part (22) having an inner hollow portion and a diameter gradually narrowed toward the upper end of the body, and an inlet (23) formed in such a manner
15 to be bent at an end of the tapered part (22) in a "┐" form for inserting the pipe (10);

fixing chips (24) mounted in the inner hollow portion of the tapered part (22) of the body (20) and formed in such a manner that the upper portion thereof is narrower and
20 the lower portion thereof is wider to correspond to the shape of the tapered part, the fixing chip(24) having at least one bolt hole (26) formed vertically therein ; and

bolts (25) perforating the inlet side of the body (20) and inserted into the bolt hole (26) of the fixing chip
25 (24), the fixing chips serving as wedge in such a manner that the fixing chips (24) are interposed between the

tapered part (22) of the body (20) and the pipe (10) when the belts are tightened.

2. The pipe fixing system according to claim 1,
5 wherein the body (20) includes a fixing plate (27) mounted on the lower 9 portion thereof and extending to the outside in such a manner to be fixed on concrete by means of bolts.

3. A pipe structure connecting system, comprising at
10 least two pipe fixing systems, each pipe fixing system including:

a body (20) having a stopping part (21) formed on the lower portion of the inside thereof for stopping the pipe (10) inserted into the body(29), an extended portion
15 extended partially upwardly from the stopping part (21) toward an upper end of the body (20) for supporting the pipe (10) and a closely contacting the outer peripheral surface of the pipe (10), a tapered part (22) having an inner hollow portion and a diameter gradually narrowed toward the upper
20 end of the body, and an inlet (23) formed in such a manner to be bent at an end of the tapered part (22) in a "┐" form for inserting the pipe (10);

fixing chips (24) mounted in the inner hollow portion of the tapered part (22) of the body (20) and formed in such
25 a manner that the upper portion thereof is narrower and the lower portion thereof is wider to correspond to the shape of

the tapered part, the fixing chip (24) having at least one or more bolt holes (26) formed vertically therein; and

bolts (25) perforating the inlet side of the body (20) and inserted into the bolt holes (26) of the fixing chip (24), the fixing chips serving as wedges in such a manner that the fixing chips (24) are interposed between the tapered part (22) of the body (20) and the pipe (10) when the bolts are tightened,

wherein the at least two pipe fixing systems are connected to each other and integrated with each other and the inlets (23) of the pipe fixing systems are arranged in different directions.

4. A pipe joint for connecting pipes, comprising at least two pipe fixing systems, each pipe fixing system including:

a body (20) having a stopping part (21) formed on the lower portion of the inside thereof for stopping the pipe (10) inserted into the body (20), an extended partially upwardly from the stopping part (21) toward an upper end of the body (20) for supporting the pipe (10) and closely contacting the outer peripheral surface of the pipe (10), a tapered part (22) having an inner hollow portion and a diameter gradually narrowed toward the upper end of the body, and an inlet (23) formed in such a manner to be bent at an end of the tapered part (22) in a "┐" form for

inserting the pipe (10);

fixing chips (24) mounted in the inner hollow portion of the tapered part (22) of the body (20) and formed in such a manner that the upper portion thereof is narrower and the lower portion thereof is wider to correspond to the shape of the tapered part, the fixing chip (24) having at least one bolt hole (26) formed vertically therein; and

bolts (25) perforating the inlet side of the body (20) and inserted into the bolt hole (26) of the fixing chip (24), the fixing chips (24) serving as wedges in such a manner that the fixing chips (24) are interposed between the tapered part (22) of the body (20) and the pipe (10) when the bolts are tightened;

and wherein the at least two pipe fixing system are connected to each other and integrated with each other and the inlets (23) of the pipe fixing system are arranged in different directions, and rubber packings (28) are embedded below the tapered parts (22) of the two pipe fixing system for maintaining sealability.

20